BioLock®

Standalone Fingerprint Door Security



The first truly weatherproof fingerprint reader for convenient, secure access to indoor or outdoor office or residential doors. Now standalone-capable, the next-generation radio-frequency scanning technology means that you never need to manage keys or cards again.

Convenient affordable security

Keys or cards are no longer the best way of controlling who can gain entry to your home or workplace. BioLock is a new-generation fingerprint reader that avoids the risk of accidental and deliberate loss or copying of keys or cards. No need for expensive cards to be cancelled and/or re-issued; no need for locks to be changed if keys or cards are lost, no risk of fraudulent or unauthorised entry.

Your BioLock can operate either completely standalone, with all functions controlled from the unit, or networked for multiple doors to a PC for instantly-available network-wide finger enrolment and audit logs, and greater customisation.

BioLock can be integrated with an exit button, any alarm or door-controller, and can connect to card-readers where casual users are not required to enrol their fingerprints.

BioLock does not require your existing door locks or hardware to be changed, and is supplied


complete with a standard electric door strike (other door release mechanisms available on request). BioLock does not require battery replacement or expensive and complicated door modification and wiring.

BioLock has myriad uses, including new-build and retrofit to residential doors, businesses of every size for external and internal doors and barriers, storerooms, server rooms, gates and barriers. Innovative uses include lighting, vehicle and machinery control.

"...this amazing product really makes keys a thing of the past."

Benefits

- Convenient no more keys or cards
- Fast enter a door faster than using a key or card
- Personal avoid keys or cards being lost
- Hassle-free no key copying or card issuing
- Simple no need for networks or PCs, easy to install



- Secure no need to change locks when you need to deny access
- Affordable easy installation, no cards or keys to issue
- Reliable radio-frequency technology reads below the skin surface, ignoring scars and dirt
- Flexible can be integrated with existing door controls and alarm systems
- Innovative can control lighting, gates, motors
- Traceable full audit logging of door entries
- Casual access optional 4-digit PIN tap-code



Standalone Fingerprint Door Security



STANDALONE BIOLOCK SYSTEM



Technical Details

- **Environment:** waterproof IP65, operating temperature $0 50^{\circ}\text{C}$ (32 122°F)
- Mounting: any flat surface via 4 screws (included) or bolts
- **Dimensions:** 75mm x 105mm x 27mm (W x H x D)
- Power: 12V DC 1A power adapter
- Colours: gloss chrome (silver) or matt black finish
- Inputs: REX Request to Exit connection, Wiegand input for proximity or other cards or barcode readers
- Outputs: relay NO/NC contact, Wiegand output on each secure relay board
- Modes: standalone, networked, or networked with emergency standalone fall-back
- **Capacity:** 100 finger templates (standalone mode), unlimited (network mode). More than 20,000 log transactions (standalone mode), unlimited(network mode).
- Communications: 10BaseT 10MB/s Ethernet LAN (required for network mode), RS485 (secure relay board)
- **Control:** built-in web-server, optional Windows[™] software
- Remote access: via built-in webserver and Ethernet
- **PIN code:** set/cancelled by web-server or finger sensor

Options

- Backup UPS power
- High-security doorstrikes for maximum-security or high-use applications
- Power over Ethernet (PoE) adapters
- BioLock Windows[™] software for time-zone control, data export
- BioClock Windows[™] software for full BioLock functionality plus time and attendance and Crystal Reports[™] employee control/payroll functions





Head Office Unit 11,Building F,16 Mars Road, Lane Cove,NSW 2066 Australia

Tel: +61 2 9882 8600 Fax: +61 2 9427 2503 Freecall: 1800 421 616 sales@brsgrp.com Multiple Patents Pending





Designed, developed & manufactured in Australia

www.brsgrp.com

BioAccess*,BioTime*,BioLock*,BioScan* and BioNet* are all trademarks of Bio Recognition Systems Pty Ltd. All information shown on this brochure is deemed to be accurate at time of printing. Bio Recognition System Pty Ltd reserves the right to change any specification and pricing without notice including discontinuing manufacture. © Copyright 2005 by Bio Recognition Systems Pty Ltd. All rights reserved. Printed in Australia. Reference BRS-BioLock® Rev1.0.