

**DS-3E0520HP-E****16 Port Gigabit Unmanaged PoE Switch**

- 12 × gigabit PoE port, 4 × gigabit Hi-PoE port, 2 × gigabit RJ45 port, and 2 × gigabit fiber optical port.
- IEEE 802.3at/af/bt standard for Hi-PoE ports (Max. 90 W PoE output).
- IEEE 802.3at/af standard for PoE ports (Max. 30 W PoE output).
- IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standard.
- 6 kV surge protection for PoE ports.
- Up to 300 m long-range transmission.
- PoE watchdog to auto detect and restart the cameras that do not respond.
- Port isolation to improve network security.
- Gigabit network access design.
- Wire-speed forwarding.
- Store-and-forward switching.
- Solid high-strength metal shell.

## ▪ Specification





Model		DS-3E0520HP-E
<b>General</b>	Shell	Metal material
	Net Weight	2.79 kg (6.15 lb)
	Gross Weight	3.60 kg (7.94 lb)
	Dimensions (W × H × D)	440.0 mm × 44.0 mm × 220.8 mm (17.3" × 1.7" × 8.7")
	Operating Temperature	0 °C to 45 °C (32 °F to 113 °F)
	Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating Humidity	5% to 95% (no condensation)
	Relative Humidity	5% to 95% (no condensation)
	Power Supply	100~240 V AC, 50/60 Hz, Max. 4 A
	Max. Power Consumption	250 W
	Power Consumption in Idle	25 W
	Installation Mode	Rack (equipped with mounting ears)
	Surge Protection	6 kV
	<b>Network Parameters</b>	Ports
MAC Address Table		8 K
Switching Capacity		40 Gbps
Packet Forwarding Rate		29.76 Mpps
Internal Cache		4.10 Mbits
<b>PoE Power Supply</b>	PoE Standard	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
	PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
	PoE Port	Hi-PoE: Ports 1 to 4 PoE: Ports 5 to 16;
	Max. Port Power	90 W
	PoE Power Budget	225 W
<b>Dialing Function</b>	Long Range	Ports 13 to 16: up to 300 m Long range performance may vary depend on camera model or cable condition.
	Port Isolation	Ports 1 to 16: port isolation mode to improve network security. Ports in an isolation group cannot communicate with each other, but they can communicate with ports outside the isolation group.
	PoE Watchdog	Ports 1 to 16: auto detect and restart the cameras that do not respond.
<b>Approval</b>	EMC	FCC (47 CFR Part 15, Subpart B), CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020), IC (ICES-003: Issue 7:2020), RCM (AS/NZS CISPR 32: 2015)
	Safety	UL (UL 60950-1), CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
	Chemistry	CE-RoHS (2011/65/EU)

## ▪ Available Model

DS-3E0520HP-E

▪ **Accessory**

▪ **Optional**

HK-SFP-1.25G-20-1550 SFP Module	HK-SFP-1.25G-20-1310 SFP Module	HK-SFP-1.25G-1310-DF-MM SFP Module	HK-SFP-1.25G-20-1310-DF SFP Module
			

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision\_Global



Hikvision  
Corporate Channel



hikvisionhq