

horizon

features

- Low profile design
- Low current draw
- 78°C activation temperature
- Remote alarm test feature
- Easy maintenance
- Remote LED option
- Designed to comply with EN54 Pt.5:2000
- Extended warranty

The HRZ-1004T high temperature heat detector is one of the Horizon range of conventional detectors.

These detectors have been produced using the latest in manufacturing technology and supplied with an array of advanced features, making them "better by design".

HRZ-1004T


conventional high temperature
(78°C) thermal detector

Data Sheet

We reserve the right to amend any design or specification in line with our policy of continuing development and improvement. © Morley-IAS Fire Systems 2004

The HRZ-1004T detector uses a state of the art class BS thermal element combined with a microprocessor, running sophisticated algorithms to provide quick and accurate detection of fires. The detection incorporates a static element and is suitable where ambient conditions normally exhibit rapid changes in temperature, eg kitchens.

A laser-based hand held Remote Test Unit can be used in conjunction with the range of Horizon detectors for alarm test purposes. The unit transmits a coded message, preventing spurious alarms being generated by other laser based devices. With a range of several metres, the hand held test unit provides an effortless way of remotely testing the Horizon range of detectors and removes the need for any direct physical access to the detector by the user.



Charles Avenue, Burgess Hill
West Sussex, RH15 9UF
United Kingdom

Tel: +44 (0) 1444 235 556
Fax: +44 (0) 1444 254 410
Email: sales@morleyias.co.uk
www.morley-ias.co.uk



A Honeywell Company



The HRZ-1004T detector also has an integral LED, which illuminates to provide a local alarm signal. This latches on, and remains illuminated until the detector is reset by a momentary power interruption. An optional remote LED annunciator may be used to repeat any alarm signal.

The detector base is fitted with a shorting spring to permit circuit testing prior to fitting the detector and has a tamper resistant feature, which when activated prevents removal of the detector without the use of a tool. All detectors are covered by our extended 3-year warranty.

electrical

Operating Voltage Range	14–28 VDC (Nominal 24VDC)
Typical Standby Current	55µA @ 24VDC
Maximum Permissible Alarm Current	80mA (current limited by control panel)

environmental

Operating Temperature Range (see note 1)	–30°C to +70°C
Storage Temperature Range	–40°C to +85°C
Humidity	5 to 95% Relative Humidity (non-condensing)

mechanical

Height (without Base)	40.5mm
Diameter	102mm
Weight	70g (+45g for standard base)
Max Wire Gauge for Terminals	1.5mm ²
Colour	Approximates to RAL9016
Material	ABS

product range

Bases

HRZ-1000BSD Standard Base
with schottky diode

accessories and other detectors

2020LT Remote Test Unit
HRZ-1002 Photoelectric/Thermal Detector
HRZ-1003 Photoelectric Detector
HRZ-1005 Rate of Rise & Fixed Temperature Thermal Detector
HRZ-1005T Fixed Temperature Thermal

Note: (1) To avoid unwanted alarm conditions being triggered by class BS detectors the maximum ambient operating temperature should not exceed 65°C.

local distributor

Every care has been taken in the preparation of this data sheet but no liability can be accepted for the use of information therein. Design features may be changed or amended without prior notice.

