

PM833

Boxed Power Supply 24 VDC - 3 A



Standard Features

- **Fault and mains present indicators**
- **Battery disconnect to prevent deep discharge**
- **Tamperswitch**
- **Fault output**
- **Mains and dc fuse**
- **Fully compliant with IEC65**
- **Transformers conform to BS145, VDE0550 & UL506**
- **Powder coated steel housing**



PM833

Boxed Power Supply 24 VDC - 3 A

Specifications

Input voltage	230 VAC
	50 Hz \pm 10%
Output voltage	27.6 VDC
Load output	2 A
Total output	3 A
Output ripple	Max. 50 mVrms
Max. battery size	7.2Ah (x2)
Battery recharge time	20
Battery disconnect voltage	19.6 \pm 0.2 VDC
Open collector output	Open circuit on fault or mains fail - 0 V - 100 mA
Fuse 12/24 V output	3 A
Fuse 230 VAC input	2 A
Operating temperature	-10 °C to +40 °C
Relative humidity	95%
Housing (steel) powder coated	1.2 mm
Dimensions (H x W x D)	275 x 330 x 80 mm

Ordering Information

Part No.	Description
PM833	Boxed power supply 24 VDC - 3 A



GE Security

www.gesecurity.com

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-PM833-2004-10-8 14:31:50 Released : 18.05.2004;