

NXG-1801-5

Secure NXG Card, 5-PACK

Product overview

The ISO card in white color offers a robust solution for a secure environment where card data is protected with Mifare DESFire EV2 smart card technology. The card is compatible with the xGenConnect security system.

The card can be linked to a user either locally via the mifare keypad NXG-1832/33-EUR or remotely via the panel web pages. The user card replaces a traditional PIN code and allows the user to fully control the xGenConnect security system as well as perform automated functions.



Details

- Standard ISO card model
- Compatible with xGenConnect
- Mifare DESFire EV2 technology
- Card data secured by AES encryption
- Printed 8-digit serial card number
- 5-pack

NXG-1801-5

Secure NXG Card, 5-PACK

Technical specifications

Technology

Credential type	Smart card
Credential operating frequency	13.56 MHz
Supported technology	Mifare DESFire EV2 (Custom data) 13.56 MHz

System

Reading distance	between 1 - 5 cm Distance may vary based on environment
Memory size	4 kB

Ordering information

Cards/tags in package	5
-----------------------	---

Physical

Material	PVC
Physical dimensions	86 x 54 x 0,8 mm
Net weight	6 g
Colour	White
Card Label	Serial number

Environmental

Operating temperature	-25 to +50°C
IP rating	IP68

UNRELEASED



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 August 2021 - 10:14