

CAST-PRO CO Fire + Smoke + Heat Multisensor c/w Voice Sounder & C-3-9.4 White VAD

Part No. **CP411VV**



Overview

- Multiple functionality in a single device - CO fire, heat & smoke multisensor fire detection plus an 86db(A) voice sounder and a C-3-9.4 VAD - detects real fires quickly, reduces false alarms effectively and indicates true alarm conditions decisively.
- Certified to EN54-3, 5, 7, 17, 23, 29 & 31.
- Compatible with C-TEC's ZFP touchscreen-controlled CAST protocol addressable fire panel.
- MASC™ (Miniature Advanced Smoke Detection Chamber) and AFFIRM™ algorithms provide incredible tolerance to false alarms whilst enhancing the detection of real fire conditions.
- Drift compensation functionality.
- Onboard short circuit loop isolator.
- Includes two 8mm x 2mm ultra-bright red LED indicating strips.
- Multiple detection modes and different sensitivities for different times of the day.
- Six selectable voice messages with tones (2 evacuate, 1 alert, 1 all clear & 2 system test messages).
- 24.9mA max. alarm current (max vol, VAD on).
- 630uA typical quiescent current @ 22-40V DC.
- Compatible with C-TEC's CA408 CAST base c/w integrated locking mechanism & ID tag.



More Information

Technical Specifications

Approvals/certifications

CPR number 0063-CPR-212190016, KIWA certified to EN54-3, 5, 7, 17, 23, 29 & 31.



| | |
|---|--|
| Compatibility | Compatible with C-TEC's ZFP CAST Addressable Fire Alarm Systems |
| Type | CO, Heat & Smoke Fire Detection plus Voice Sounder & White VAD |
| Sensitivity | 12 Detection Modes (default for this device is Mode 10). |
| Supply wiring | 2-wire, polarity sensitive. |
| Supply/operating voltage | 28 to 40V DC. |
| Quiescent current | 630uA @ 40V. |
| Alarm current (Imax at Vmin) | 24.9mA (max volume, VAD lit). |
| Alarm current (Iavg at Vmin) | 14.6mA (max volume, VAD lit). |
| Sound pressure level (LAFmax) at Vmax at 1m | 86dB(A). |
| VAD category & coverage | C-3-9.4 (10m ² /mA efficiency; 0.5Hz Synchronised). |
| Indicators | 2 LED indicator strips emitting red light when in alarm offering 360° visibility. Optional remote LED. |
| Connections | Via CA408 base: 1 +Ve IN (analogue switch); 2 +Ve OUT (analogue switch); 3 Remote LED +Ve; 4 0V; 5 0V; 6 Screen; 7 Screen. |
| Product dimensions (mm) | 105mm diameter x 51mm deep (detector only); 105mm diameter x 68mm deep (detector in base). |
| IP Rating | IP21C |
| Weight | 134g (not in base); 189g (in base). |
| Operating conditions/temperature | -10°C to +50°C. Max relative humidity: 95% (non-condensing) |
| Notes | Requires a CA408 CAST base. CA408R relay base also available. |



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom