

## **NX-7-EUR**

6-16 zone panel in small polycarbonate housing

### **Overview**

The NX-7 is a full-featured security system that uses advanced technology for burglary, fire and environmental detection. It is a flexible security system that is both easy to install and simple to use. With two partitions and up to 16 zones, it can handle big or small residential and light commercial security needs.

### **High Standards**

The panel comes standard with 6 wired zones. Two programmable outputs can be set up to activate external devices during an alarm or other system event. The modular design allows for complete integration within one enclosure. Expanding capability is fast and easy.

### **Effortless Programming**

Conduct quick and easy on-site programming with the keypads using Menu's or Locations or via the onboard USB port connected to your laptop with DL900 Up and Download software. Off-site programming is also available with the DL900 software for Windows via PSTN, IP or GSM.



### **Standard Features**

- 6 hardwired zones onboard
- Expandable up to 16 wireless zones
- Menu-driven or location programming
- 2 partitions
- 512 events log file
- USB port for PC programming and software update
- EN 50131 Grade 2 Class 2 Certified



# NX-7-EUR

6-16 zone panel in small polycarbonate housing

## Specifications

<b>Supply voltage (typical)</b>	230 Vac, 50 Hz, 25 VA
<b>Operating power (nominal)</b>	16.5 Vac/50 Hz
<b>Battery</b>	Max. 12 Vdc/7.2 Ah
<b>Auxiliary power</b>	1.2 A
<b>Output voltage</b>	13.8 V +/- 2%
<b>Number of zones</b>	
Wired onboard	6
Wireless (optional)	16 max
<b>PIN codes</b>	99 (4 digits) or 66 (6 digits)
<b>Partitions</b>	2
<b>Logfile (events)</b>	512
<b>Outputs</b>	
Relays	2 x 1.1A at 13.8V +/- 10% (2 SPDT)
Supervised Siren Output	1 x 1A at 13.8V +/- 10%
<b>Loop resistance</b>	3K3 Ohm
<b>Operating temperature</b>	-10° to 55°C
<b>Dimensions</b>	
Housing	225 x 256 x 113 mm
<b>Humidity</b>	Max 95%, non condensing
<b>Shipping weight</b>	1.7 Kg

## Ordering Information

Part No.	Description
NX-7-EUR	6-16 zone panel in small polycarbonate housing

