



# TX-2511-03-1

## Wireless DUAL 12m PI 868gen2. 12m

### One way transmitter

The sensor has a chip tuned wireless transmitter that communicates with a 868AM Gen2 receiver such as, for example the ATS1235. The learn-in process of the sensor is identical to the process used with legacy sensors. Each sensor reports a unique ID code with each transmission. The sensor also reports the battery and transmitter condition (supervisory signal) to the panel every 18 minutes.

### Patented Range Gated Radar Technology

This series of wireless motion sensors incorporate a Carrier Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection range. Every motion sensor comes with four possible radar ranges selectable via jumpers allowing the detection range to be tailored according to the room where the motion sensor is installed. The radar operates on 5.8GHz frequency and will not interfere with any WiFi networks.

### PIR combined with mirror power

The patented optical mirror technology gives the advantage of gliding focus, which creates a volumetric detection curtain from floor level up to installation height resulting in a sensor that never loses track of the object.

In these series we are using a dual element digital pyro generating two volumetric curtains for each of the nine curtain sets.

### Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within their detection coverage.

But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

### Ease and flexibility of installation

- 1.Easy opening and closing system.
- 2.Easy access when changing the batteries.
- 3.Easy access to mirror optics.
- 4.Tolerates wall angle deviation and different mounting heights.
- 5.One mounting plate for all sensors in the series.

### Other members of the family

This family includes motion sensors with variants in detection ranges



### Details

- Patented selectable range gated radar technology clearly defining the radar detection border
- PIR technology with patented mirror curtain optics
- Intelligent alarm decision based on signal classification of the PIR and radar alarm
- Full under-crawl detection
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- End-user friendly product design for exchanging batteries
- 3-years battery life with 2 batteries
- PetImmune functionality
- Holding several security approvals (pending)

and a Pet Immune variant.

The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

# TX-2511-03-1

## Wireless DUAL 12m PI 868gen2. 12m

### Technische specificaties

#### Algemeen

Technologie	Dual
Type toepassing	Muurmontage
Anti-maskering	Nee
Ongevoelig voor huisdieren	Ja
Camera	Nee
Opstarttijd detector	1 minute

#### Detectie

Max. detectiebereik	12 m
Detectiebereik selectie	4, 6, 9 and 12 m
Aantal gordijnvelden	9
Openingshoek (kijkveld)	86°
Microgolffrequentie (nom.)	5.8 GHz
Onderkruipbeveiliging	Ja
Doel snelheidsbereik	0.3 m/s to 3 m/s

#### Bedraad / draadloos

Bedraad / draadloos	Draadloos
Draadloze frequentie	868 MHz AM

#### Elektrisch

Stroomverbruik	58 µA (average), 50 mA (max.)
Batterijen	2 x 3.0 V (1300 mAh lithium)
Batterij levensduur	3 years

#### Fysiek

Fysieke afmetingen	130 x 69 x 53 mm
Netto gewicht	176 g (including two batteries)
Kleur	Wit
Montagehoogte	2.3 to 3 m, EN 2.3 to 2.6 m

#### Omgeving

Bedrijfstemperatuur	-10 to 55° C
Relatieve vochtigheid	95% max. condensing
Omgeving	Binnen
IP-classificatie	IP30 / IK02

#### Regelgeving

EN50131 Grade	Grade 2
---------------	---------



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar [nl.firesecurityproducts.com](http://nl.firesecurityproducts.com) of neem contact op met uw verkoopvertegenwoordiger.